



SYNMAR QUINTUS 5W-40 | S100005

V170622

Description

The Synmar Quintus 5W-40 is a fully synthetic motor oil based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a good detergency and dispersion
- a safe lubrication film at high temperatures
- a strong protection against wear, corrosion and foaming

Application

The Synmar Quintus 5W-40 is an all-round motor oil which is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Performance Level

ACEA A3/B4
 API CF
 API SN
 Fiat 9.55535-H2/M2
 GM-LL-B-025
 MB 229.3/229.5
 Porsche A40
 PSA B71 2296/PSA B71 2293
 Renault RN0700/RN0710
 VW 502.00/505.00

Typicals

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	6100
Viscosity 40 °C, mm ² /s	80,30
Viscosity 100 °C, mm ² /s	13,10
Viscosity Index	165
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,2
Sulphate Ash, %	1,26