



## SYNMAR AURELIUS 0W-30 | S100006

### Description

The Synmar Aurelius 0W-30 is a fully synthetic, fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- a lower fuel consumption
- suitable for modern catalysts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Application

The Aurelius 0W-30 is a fully synthetic, fuel economy, "mid SAPS" motor oil which is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

### Performance Level

Performance level  
ACEA C2  
PSA B71 2290  
PSA B71 2312  
Fiat 9.55535-GS1/DS1

### Typicals

Density at 15 °C, kg/l	0,842
Viscosity -30 °C, mPa.s	5920
Viscosity 40 °C, mm <sup>2</sup> /s	55,10
Viscosity 100 °C, mm <sup>2</sup> /s	9,8
Viscosity Index	165
Flash Point COC, °C	230
Pour Point, °C	-51
Total Base Number, mgKOH/g	6,2
Sulphate Ash, %	0,54