

## SYNMAR QUINTUS 10W-40

<b>Description</b>	Synmar Quintus 10W-40 is based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained: <ul style="list-style-type: none"><li>- a high and stable viscosity index</li><li>- a fast cold start</li><li>- a strong resistance against oxidation</li><li>- a good detergency and dispersion</li><li>- a safe lubrication film at high temperatures</li><li>- a strong protection against wear, corrosion and foaming</li></ul>	
<b>Application</b>	This all-round motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.	
<b>Performance Level</b>	Performance level ACEA A3/B4 API SN/CF MB 229.1/229.3 VW 501.01/505.00 RENAULT RN0700	
<b>Typicals</b>	Density at 15 °C, kg/l	0,860
	Viscosity -25 °C, mPa.s	4930
	Viscosity 40 °C, mm <sup>2</sup> /s	90,40
	Viscosity 100 °C, mm <sup>2</sup> /s	13,70
	Viscosity Index	154
	Flash Point COC, °C	224
	Pour Point, °C	-39
	Total Base Number, mgKOH/g	10,4
	Sulphate Ash, %	1,31