



SYNMAR MAXIMUS 0W-30 | S100021

V170622

Description

Synmar Maximus 0W-30 is a fully synthetic motor oil for use in passenger cars and light duty commercial vehicles. This oil can be used in cars with turbo charged engines, catalytic converters and direct fuel injection diesel engines.

Synmar Maximus 0W-30 provides an extremely rapid and stable lubricant film at the cold start and maintains this film at high operating temperatures

Next to this, this oil offers an extremely high oxidation stability and wear protection. Both engine and oil stay clean, even after prolonged drain intervals (up to 30.000 km).

Application

Synmar Maximus 0W-30 offers extra fuel saving properties and can be mixed with both synthetic and mineral motor oils, although especially for this oil, mixing with other oils will not benefit the outstanding quality of the products.

Synmar Maximus 0W-30 meets the MB 229.5 specification and can be used for an intensive and prolonged use.

Performance Level

ACEA A3/B4
API SL
MB 229.3/229.5
Renault RN0700/Renault RN0710
Volvo 95200356
VW 502.00/505.00

Typicals

Density at 20 °C, kg/l	0.841 kg/l
Viscosity 40 °C, mm ² /s	68.2 cSt
Viscosity 100 °C, mm ² /s	12.2 cSt
Flash Point COC, °C	179
Pour Point, °C	-54 °C