



## SYNMAR MAXIMUS 0W-40 | S100022

V170622

### Description

Synmar Maximus 0W-40 is a fully synthetic motor oil for use in passenger cars and light duty commercial vehicles. This oil can be used in cars with turbo charged engines, catalytic converters and direct fuel injection diesel engines.

Synmar Maximus 0W-40 provides an extremely rapid and stable lubricant film at the cold start and maintains this film at high operating temperatures.

### Application

Synmar Maximus 0W-40 offers extra fuel saving properties and can be mixed with both synthetic and mineral motor oils, although especially for this oil, mixing with other oils will not benefit the outstanding quality of the products.

Synmar Maximus 0W-40 meets the MB 229.5 specification and can be used for an intensive and prolonged use.

### Performance Level

ACEA A3/B4  
API SN  
BMW Longlife-01  
Fiat 9.55535-H2/M2/N2/Z2  
Ford WSS-M2C937-A  
MB 229.3/229.5  
Porsche A40  
Renault RN0700/Renault RN0710  
VW 502.00/505.00

### Typicals

Density at 20 °C, kg/l	0.841 kg/l
Viscosity 40 °C, mm <sup>2</sup> /s	73.5 cSt
Viscosity 100 °C, mm <sup>2</sup> /s	13.1 cSt
Flash Point COC, °C	207
Pour Point, °C	-45 °C