



SYNMAR ORLANDO 10W-40 | S200001

Description

Synmar Orlando 10W-40 is a top-quality diesel engine oil based on the latest additive technology combined with synthetic base oils. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against wear, corrosion and foam
- a high and stable viscosity index
- a low sulphated ash number
- prolonged oil drain intervals

Application

Synmar Orlando 10W-40 has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for Euro 5 and Euro 6 engines in combination with diesel fuel with a low sulphur content. This engine oil is also suitable for application in engines with or without particle filters and exhaust catalysts. This motor oil is one of the group "low SAPS" lubricants.

Performance Level

ACEA E4, E6, E7, E9
 API CK-4
 Deutz DQC IV-10 LA
 Mack EO-O Premium Plus
 MAN M 3477/M 3575/M 3271-1
 MB 228.31/228.51
 Scania Low Ash
 Volvo VDS-4, Renault VI RLD-3
 Cat ECF-3
 Cummins CES 20081
 Detroit Diesel 93K218
 JASO DH-2
 MTU Type 3.1/2.1
 Renault VI RLD-2

Typicals

Density at 15 °C, kg/l	0,857
Viscosity -25 °C, mPa.s	6670
Viscosity 40 °C, mm ² /s	90,70
Viscosity 100 °C, mm ² /s	13,60
Viscosity Index	152
Flash Point COC, °C	218
Pour Point, °C	-33
Total Base Number, mgKOH/g	12,8
Sulphate Ash, %	0,98