



SYNMAR ACARIO 15W-40 | S200150

V260822

Description	The Synmar Acario 15W-40 is a mineral multigrade motor oil based on high quality base oils to which balanced additive components have been added in order to assure a high and stable viscosity index.	
Application	The Synmar Acario 15W-40 is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.	
Approval	Volvo VDS-3 Mack EO-N Renault RLD-2	
Performance Level	ACEA E7 API CI-4/SL Caterpillar ECF-1-A Caterpillar ECF-2 CES 20076/20077/20078 Detroit Diesel DDC 93K215 Deutz DQC III-10 Global DHD-1 Mack EO-M Plus Mack EO-N MAN M3275 MB 228.3 MTU type 2 Renault RLD Renault RLD-2 Volvo VDS-3	
Typicals	Density at 15 °C, kg/l	0,878
	Viscosity -20 °C, mPa.s	6500
	Viscosity 40 °C, mm ² /s	98,00
	Viscosity 100 °C, mm ² /s	13,30
	Viscosity Index	134
	Flash Point COC, °C	212
	Pour Point, °C	-36
	Total Base Number, mgKOH/g	11,1
	Sulphate Ash, %	1,43