



SYNMAR ALEXIUS MULTI VEHICLE | S300000

V170622

Description

The Synmar Alexius Multi Vehicle is a synthetic automatic transmission fluid, based on synthetic base oils, formulated with special friction modifiers to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- an excellent stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties and consequently low noise and smooth switching
- compatible with synthetic seals
- a quick oil provision at cold start conditions
- without dye

Application

The Synmar Alexius Multi Vehicle may be used for automatic transmissions of passenger cars and commercial vehicles. It is recommended to follow the instructions of the manufacturer.

Performance Level

Allison C-4/TES 295/TES 389
ATF LT 71141
Caterpillar TO-2
Dexron III H/III/IIID/
ETL 7045
Ford Mercon/Mercon V/WSS-M2C138-CJ/WSS-M2C166-H/WSS-
M2C202-B
Honda Z1 (except CVT)
Hyundai/Mitsubishi SP, SP-II, SP-III & Dia Queen J2
Idemitsu K17
Isuzu besco ATF-II,ATF-III
JASO M 315 1A
JATCO 3100 PL 085
JWS 3309/3314/3317
MAN 339 Type Z1/V1 & Z2
Mazda M-III, M-5
MB 236.1/236.11
Mopar ATF +3 (MS 7176E)
Mopar ATF +4 (MS-9602)
Nissan Matic D, J, K
Subaru KO410Y0700
Toyota /Lexus T, T-II, T-III, T-IV
Voith G607/G1363
Volvo 1161540
Volvo 97341
VW G 052 162/VW G 052 990/VW G 055 025
ZF TE ML 03D/04D/09X 11B /14B/17C

Typicals

Density at 15 °C, kg/l	0,843
Viscosity 40 °C, mm ² /s	35,50
Viscosity 100 °C, mm ² /s	7,63
Viscosity Index	192
Flash Point COC, °C	214
Pour Point, °C	-54