



SYNMAR ALEXIUS VI | S30002

V170622

Description

The Synmar Alexius VI is a very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- a very strong dispersion, therefore sludge is restricted to a minimum
- a very low pour point
- very good stability against oxidation and thermal properties
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- longer life time of the liquid
- exceeds the properties of Dexron III and II liquids

Application

The Synmar Alexius VI may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared with older Dexron types. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended.

Performance Level

Aisin Warner AW-1
Bentley Oil PY112995PA
CHRYSLER 68157995AA
DSI H 6-SPEED TRANSMISSION (AT 3292)
Fiat 9.55550-AV2
Fiat 9.55550-AV5
Ford WSS-M2C924-A
GM Dexron VI
Honda ATF DW-1
HYUNDAI NWS-9638
Hyundai SP IV, SPH-IV
JAGUAR 02JDE26444
Jaguar Fluid 8432
JWS 3324 (ATF WS)
LAND ROVER LR023288
Land Rover TYK 500050 M-1375.4
Maserati 231603
Mazda FZ MB 236.12
MB 236.41
Mercon LV/SP Mitsubishi SP-IV & ATF J-2
Nissan Matic S
SAAB 93 165 147
Toyota Type WS (JWS 3324)
VW G 055 005 / G 055 162 / G 055 540 / G 060 162

Typicals

Density at 15 °C, kg/l	0,843
Viscosity 40 °C, mm ² /s	29,60
Viscosity 100 °C, mm ² /s	5,90
Viscosity Index	149
Flash Point COC, °C	212
Pour Point, °C	-51
Total Base Number, mgKOH/g	2,7