



## SYNMAR ALEXIUS III G | S300154 V23-1404

### Description

Synmar Alexius III G is a very high graded automatic transmission fluid formulated with solvent refined and synthetic base oils and a number of selected additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

### Application

The Synmar Alexius III G may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF or IIIG fluid is required.

### Performance Level

Allison C4  
CAT TO-2  
Ford Mercon  
GM Dexron IIIG  
MAN 339 Z1, V1, Z2, V2  
MB 236.1, 236.5, 236.6, 236.7, 236.9  
Voith 55.6335, 55.6636  
Volvo 97340, 97341  
ZF TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A, 14B, 16L, 17C

### Typicals

Color	Red
Density at 15 °C, kg/l	0,840
Viscosity 40 °C, mm <sup>2</sup> /s	34
Viscosity 100 °C, mm <sup>2</sup> /s	7,70
Viscosity Index	200
Flash Point COC, °C	180
Pour Point	<-40

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.

#### SYNMAR B.V.

Albert Schweitzerstraat 7, 7131 PG Lichtenvoorde, The Netherlands  
T: +31 (0) 33 303 3044 | M: [info@synmar.nl](mailto:info@synmar.nl)