



SYNMAR CHAINSAW OIL 220| S400401 V24-1402

Description	Synmar Chainsaw Oil 220 is based on a high-quality aromatic base oils, to which a special additive package has been added to improve the adhesive power on the blade and the chain and prevent the oil from letting loose. In addition, the Synmar Chainsaw Oil 220 has excellent properties for both lubrication and cooling of the saw blade and the saw chain.
Application	Synmar Chainsaw Oil 220 has been specially developed to lubricate and cool the saw chain of chainsaws, preventing it from seizing or breaking. The high adhesive power of this chainsaw oil prevents the oil from letting loose.

Please note: This chainsaw oil is not suitable for lubricating the drive motor

Performance Level

Typicals	Color	Amber
	Density at 15°C, kg/l	0.893
	Viscosity 40 °C, mm²/s	220
	Viscosity 100 °C, mm²/s	19
	Viscosity Index	98
	Flash Point COC, °C	255
	Pour Point, °C	-15

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.

SYNMAR B.V.

Albert Schweitzerstraat 7, 7131 PG Lichtenvoorde, The Netherlands T: +31 (0) 33 303 3044 | M: info@synmar.nl