



SYNMAR MARINE 15W-40 | S800150

Description Synmar Marine 15W-40 is a robust motor oil, developed according to the latest oil usage and emission requirements, and fulfils all current quality requirements for European as well as American and Japanese diesel oils.

Application The Synmar Marine 15W-40 is pre-eminently suited for heavy diesel engines, but can also be used in petrol, LPG and light diesel motors, whether or not they are equipped with a turbo and/or catalytic converter and/or common rail.

Performance Level

- ACEA E7
- API CI-4/SL
- Cat ECF-1-a/ECF-2
- Cummins CES 20077/20078
- Detroit Diesel 93K215
- Deutz DQC III-10
- Global DHD-1
- JASO DH-1
- Mack EO-N/EO-M Plus
- MAN M 3275-1
- MB 228.3
- MTU Type 2
- Renault VI RLD-2
- Volvo VDS-3

Typicals	Density at 15 °C, kg/l	0,878
	Viscosity -20 °C, mPa.s	6500
	Viscosity 40 °C, mm ² /s	98,00
	Viscosity 100 °C, mm ² /s	13,30
	Viscosity Index	134
	Flash Point COC, °C	212
	Pour Point, °C	-36
	Total Base Number, mgKOH/g	11,1
	Sulphate Ash, %	1,43