



SYNMAR EMPANDA 75W GL-4 | S300103

V170622

Description

Synmar Empanda 75W GL-4 is a full synthetic gear oil, which can be used in final drives and manual transmissions.

Synmar Empanda 75W GL-4 is very well compatible with synchromesh and ensures very smooth shifting even at low temperatures.

Synmar Empanda 75W GL-4 contains special friction modifiers, which ensure sustainable fuel saving and less heat development.

Application

Synmar Empanda 75W GL-4 ensures adequate lubrication at both very low, as very high temperatures and protects against corrosion, wear, thickening and deposits.

Synmar Empanda 75W GL-4 is compatible with most elastomers and seal materials and does not foam under extreme loads.

Performance Level

API GL-4
 BMW 23 00 1 434 404, 23 00 7 533 818, 83 22 0 396 706, 83 22 2 239 654, 83 22 2 239 655, 83 22 2 167 666, 83 22 2 156 969
 Fiat 9.55550-MZ2
 Ford WSS-M2C200-D2
 GM 95599883
 Jaguar Land Rover GX73-M1R564-AA
 MB 235.10/235.71/236.24
 Nissan 32001 1BY0A, LV MTF-1
 PSA 9730 A8
 Toyota 08885-81001, 08885-81081;
 VW G 052 171 A1/A2 (TL 521 71)/G 052 178 A2 (TL521 78)/
 G 052 512 A2 (TL 525 12)/G 052 527 A2/G052 549/G 052 798/
 G 052 726 A2/G 055 726 A2/G 060 726 A2/G 070 726 A2

Typicals

Color	Light yellow
Density at 20 °C, kg/l	0.877 kg/l
Viscosity 40 °C, mm ² /s	40.8 cSt
Viscosity 100 °C, mm ² /s	6.7 cSt
Flash Point COC, °C	221
Pour Point, °C	-44 °C