



## SYNMAR ALBERTUS 5W-30 | S100003

### V24-3009

#### Description

The Synmar Albertus 5W-30 Synmar Albertus 5W-30 is a modern, fully synthetic, fuel-efficient motor oil suitable for most Ford petrol and diesel engines from 2012 onwards. Synmar Albertus 5W-30 can also be used for all models requiring Ford specifications WSS-M2C-921A and 913A/B/C.

#### Application

The Synmar Albertus 5W-30 is a fuel economy motor oil which is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below. This motor oil is specially developed for those cars, that ask for motor oils that fulfill the recent requirements of the OEM's. This oil is fully backward compatible with Ford M2C 913-A, B and C.

#### Performance Level

ACEA A5/B5  
 API SN/CF  
 BMW LL-01 FE  
 Fiat 9.55535-G1/N1

Ford WSS-M2C913-D/C/B/A  
 Renault RN0700  
 STJLR 03.5003

#### Typicals

|                            |       |
|----------------------------|-------|
| Density at 15 °C, kg/l     | 0,845 |
| Viscosity -30 °C, mPa.s    | 3890  |
| Viscosity 40 °C, mm²/s     | 54,50 |
| Viscosity 100 °C, mm²/s    | 9,90  |
| Viscosity Index            | 170   |
| Flash Point COC, °C        | 220   |
| Pour Point, °C             | -39   |
| Total Base Number, mgKOH/g | 10,1  |
| Sulphate Ash, %            | 1,09  |

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.