



SYNMAR ACARIO 15W-40 | S200150

V26-1708

Description

The Synmar Acario 15W-40 is a mineral multigrade motor oil based on high quality base oils to which balanced additive components have been added in order to assure a high and stable viscosity index.

Application

The Synmar Acario 15W-40 is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.

Performance Level

ACEA E7	Global DHD-1
API CI-4/SL	JASO DH-1
Allison C3	Mack EO-M Plus / EO-N
Cat ECF-1-A / ECF-2 / TO-2	MAN M3575-1
CES 20077/20078	MB 228.3
Detroit Diesel DDC 93K215	MTU Type 2
Deutz DQC III-18	Renault RLD / RLD-2
ZF 04C / 04P / 07C / 07D / 21K	Volvo VDS-3

Typicals

Colour	Amber
Density at 15 °C, kg/l	0,867
Viscosity -20 °C, mPa.s	6500
Viscosity 40 °C, mm²/s	98,00
Viscosity 100 °C, mm²/s	14,40
Viscosity Index	147
Flash Point COC, °C	212
Pour Point, °C	-36
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.