



SYNMAR AGRI STOU 15W-40 | S400603

Description

Synmar Agri STOU 15W-40 is an up-to-date multifunctional lubricating oil for agricultural- and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to achieve the following properties:

- a powerful dispersion and detergency
- a high activity against wear, corrosion and foam
- a very strong resistance to oxidation
- an excellent extreme pressure properties
- a high and stable viscosity index

Application

Synmar Agri STOU 15W-40 (*) has been developed to achieve one single lubricating oil that is able to lubricate:

- gasoline engines
- diesel engines (with or without turbo-charging)
- transmissions (also "wet" brakes)
- hydraulic systems

(*) a so-called Super Tractor Oil Universal = STOU

Performance Level

API SF/CG-4/GL-4
ACEA E3, MIL-L-2104D
John Deere J27
Massey Ferguson CMS M1144/M1145
MB 227.1
ZF TE-ML 06B/07B
Allison C4
Cat TO-2
Ford M2C134-D
John Deere J20C
Massey Ferguson CMS M1143

Typicals

Density at 15 °C, kg/l	0,874
Viscosity -20 °C, mPa.s	4760
Viscosity 40 °C, mm ² /s	93,50
Viscosity 100 °C, mm ² /s	14,50
Viscosity Index	137
Flash Point COC, °C	218
Pour Point, °C	-36
Total Base Number, mgKOH/g	10,7
Sulphate Ash, %	1,45