



## SYNMAR MARCUS 5W-30 | S100015 V24-3009

### Description

Synmar Marcus 5W-30 is a fuel economy, universal motor oil, developed according to the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- a lower fuel consumption
- suitable for modern catalysts
- a fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Application

Synmar Marcus 5W-30 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters.

### Performance Level

ACEA C2  
API SN/CF  
Fiat 9.55535-S1  
PSA B71 2290  
Renault RN0700

### Typicals

Density at 15 °C, kg/l	0,848
Viscosity -30 °C, mPa.s	5390
Viscosity 40 °C, mm <sup>2</sup> /s	63,00
Viscosity 100 °C, mm <sup>2</sup> /s	10,90
Viscosity Index	166
Flash Point COC, °C	230
Pour Point, °C	-42
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,80

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.