



SYNMAR VARIUS 0W-20 | S100019

V24-3009

Description

Synmar Varius 0W-20 is a fully synthetic fuel-saving motor oil for passenger car petrol and diesel engines, for the most recent Volvo engines in particular.

Synmar Varius 0W-20 provides an extremely quick and stable lubricant film at the cold start at low temperatures and offers high thermal stability under heavy duty operating conditions.

Application

Synmar Varius 0W-20 is intended for the new Volvo Engine Architecture (VEA engines) technology. Synmar Varius 0W-20 is equipped with the most recent VOLVO VCC RBS0-2AE specification for both petrol and diesel versions in Volvo vehicles.

Performance Level

ACEA C5
API SN/CF
Chrysler MS-6395
ILSAC GF-6A
Volvo VCC RBS0-2AE

Typicals

Density at 20 °C, kg/l	0.842 kg/l
Viscosity 40 °C, mm ² /s	47.1 cSt
Viscosity 100 °C, mm ² /s	9 cSt
Viscosity Index	175
Viscosity, dynamic (CCS)	5687 cP
Sulphated ash	0.8wt%
Flash Point COC, °C	200
Pour Point, °C	-48 °C

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.