



## SYNMAR MAGNUS 10W-30 | S100103

### V24-0810

#### Description

Synmar Magnus 10W-30 is a synthetic motor oil based on special base oils that have a natural high viscosity index, to which additives are added to obtain the following properties:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a safe lubrication film at high temperature
- a good detergency and dispersion
- a strong protection against wear, corrosion and foaming

#### Application

The Synmar Magnus 10W-30 is a universal motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

#### Performance Level

ACEA A3/B3, A3/B4  
API SL/CF  
MB 229.1

#### Typicals

Density at 15 °C, kg/l	0,866
Viscosity -30 °C, mPa.s	6620
Viscosity 40 °C, mm <sup>2</sup> /s	89,30
Viscosity 100 °C, mm <sup>2</sup> /s	13,50
Viscosity Index	153
Flash Point COC, °C	216
Pour Point, °C	-39
Total Base Number, mgKOH/g	8,3
Sulphate Ash, %	1,08

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.