



SYNMAR MARIUS 20W-50 | S100151 V24-0810

Description

Synmar Marius 20W-50 is a universal multigrade engine oil produced with special selected solvent refined base oils and additives, which are adapted to the mentioned application. This engine oil has the following properties:

- a good detergency prevents deposits in the engine
- a good dispersion that prevents from precipitation and sludge
- a powerful action against wear, corrosion and foam
- a stable viscosity index
- low ash contents

Application

The Synmar Marius 20W-50 is suitable for the older types gasoline or diesel engines, with or without super-charging.

Performance Level

ACEA A3/B3, E2
API SJ/CG-4
Allison C-4
MB 228.1/228,3
MAN 271
Volvo VDS
MTU type 2
Mack EO/L

Typicals

Density at 15 °C, kg/l	0,888
Viscosity -20 °C, mPa.s	7600
Viscosity 40 °C, mm ² /s	154,30
Viscosity 100 °C, mm ² /s	17,30
Viscosity Index	122
Flash Point COC, °C	226
Pour Point, °C	-30
Total Base Number, mgKOH/g	11
Sulphate Ash, %	1,43

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.