



SYNMAR ROLLO 10W-40 | S200000 V24-0810

Description	The Synmar Rollo 10W-40 is a fully synthetic LOW-SAPS motor oil for commercial vehicles. It is a top quality, fuel saving diesel motor oil based on the latest technology.	
Application	The Synmar Rollo 10W40 has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for Euro 4, Euro 5 and Euro 6 engines in combination with diesel fuel with a low sulphur content. This engine oil is also suitable for application in engines with or without particle filters and exhaust catalysts. This motoroil is one of the group "low SAPS" lubricants.	
Performance Level	ACEA E6, E7, E9 API CI-4 Cat ECF-1 Cummins CES 20076/20077 DAF Extended Drain Deutz DQC IV-18 LA Iveco 18-1804 TLS E6 JASO DH-2 Mack EO-N MAN M 3477 / M 3271-1 MB 228.51 MTU Type 3.1 Renault VI RLD-2/RXD/RGD Volvo VDS-3	
Typicals	Density at 15 °C, kg/l Viscosity -25 °C, mPa.s Viscosity 40 °C, mm ² /s Viscosity 100 °C, mm ² /s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Sulphate Ash, %	0,860 5990 90,00 13,70 155 222 -36 10,0 0,95

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.