



## SYNMAR ACARIO 15W-40 | S200150 V24-1212

<b>Description</b>	The Synmar Acario 15W-40 is a mineral multigrade motor oil based on high quality base oils to which balanced additive components have been added in order to assure a high and stable viscosity index.	
<b>Application</b>	The Synmar Acario 15W-40 is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.	
<b>Approval</b>	Volvo VDS-3 Mack EO-N Renault RLD-2	
<b>Performance Level</b>	ACEA E7 API CI-4/SL Caterpillar ECF-1-A Caterpillar ECF-2 CES 20076/20077/20078 Detroit Diesel DDC 93K215 Deutz DQC III-10 Global DHD-1	Mack EO-M Plus Mack EO-N MAN M3575 MB 228.3 MTU Type 2 Renault RLD Renault RLD-2 Volvo VDS-3
<b>Typicals</b>	Density at 15 °C, kg/l Viscosity -20 °C, mPa.s Viscosity 40 °C, mm <sup>2</sup> /s Viscosity 100 °C, mm <sup>2</sup> /s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Sulphate Ash, %	0,867 6500 98,00 14,40 147 212 -36 11,1 1,43

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.