



SYNMAR NOVUS SAE 50 | S200162 V24-1212

Description

The Synmar Novus SAE 50 is an universal engine oil produced with high quality solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:

- an excellent detergency preventing from deposits in the hot zones of the engine
- a very active dispersion, that prevents from precipitation and sludge
- a powerful action against wear, corrosion and foam
- low ash contents

Application

The Synmar Novus SAE 50 is suitable for gasoline and diesel engines, with or without supercharging.

Performance Level

API SG/CF/CF-2
API CF-4
MB 228.0/228.1
MAN 270/271
Deutz DQC I-02

Typicals

Density at 15 °C, kg/l	0,890
Viscosity 40 °C, mm ² /s	215,00
Viscosity 100 °C, mm ² /s	18,80
Viscosity Index	98
Flash Point COC, °C	255
Pour Point, °C	-6
Total Base Number, mgKOH/g	3,0
Sulphate Ash, %	0,91

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.