



## SYNMAR EMPANDA 75W-80 FE GL-4 | S300102 V25-2503

### Description

Synmar Empanda 75W-80 FE GL-4 is a fully synthetic, universal gear oil which can be applied in manual gearboxes with or without a retarder or intarder where an API GL-4 specification is prescribed.

Synmar Empanda 75W-80 FE GL-4 is recommended for i.e. Mercedes, MAN, IVECO, DAF, Volvo and Renault trucks.

### Application

Synmar Empanda 75W-80 FE GL-4 is a relatively thin oil, enabling smooth shifting at low temperatures, partially due to a low pour point. Due to the high viscosity index, a good lubricity at high temperatures is guaranteed.

### Performance Level

API GL-4  
MB 235.28  
MAN 341 Z-5  
Volvo 97307  
Voith Class B  
ZF TE-ML 01E  
ZF TE-ML 02E  
ZF TE-ML 16P

### Typicals

Colour	Amber
Density at 20 °C, kg/l	0.854 kg/l
Viscosity 40 °C, mm <sup>2</sup> /s	54 cSt
Viscosity 100 °C, mm <sup>2</sup> /s	9.4 cSt
Flash Point COC, °C	157
Pour Point, °C	-42 °C

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.