



SYNMAR ALEXIUS II D | S300153

V25-2503

Description

The Synmar Alexius II D is a very high graded automatic transmission fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

Application

The Synmar Alexius II D may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required.

Performance Level

Allison C4
 Caterpillar TO-2
 Ford Mercon, M2C138-CJ, M2C166-H
 GM Dexron II. IID
 MB 236.1, 236.7
 ZT TE-ML 09, 11, 14

Typicals

Colour	Red
Density at 15 °C, kg/l	0,866
Viscosity 40 °C, mm ² /s	43,20
Viscosity 100 °C, mm ² /s	8,25
Viscosity Index	168
Flash Point COC, °C	198
Pour Point, °C	-45
Total Base Number, mgKOH/g	1,5
Sulphate Ash, %	0,18

The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this overview is composed with the most possible care, Synmar does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors.