

Organic G11-ALU Coolant -36 LLVersion number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name	Organic G11-ALU Coolant -36 LL
Unique formula identifier (UFI)	C520-E0UK-500K-7G92
Article number	S500011

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Coolant Professional use Consumer use
--------------------------	---

1.3 Details of the supplier of the safety data sheetSynmar B.V.
Albert Schweitzerstraat 7
7131 PG Lichtenvoorde
NetherlandsTelephone: +31 (0) 33 303 3044
e-mail: info@synmar.nl
Website: www.synmar.nle-mail (competent person) info@synmar.nl**1.4 Emergency telephone number**

Emergency information service	+31 (0) 33 303 3044 This number is only available during the following office hours: Mon-Fri 09:00 - 17:00
-------------------------------	---

Poison centre		
Country	Name	Telephone
United Kingdom	National Poisons Information Service (NPIS)	0344-8920111 (medical professionals only)
United Kingdom	NHS (general public)	non-emergency: 111 or a doctor; emergency: 999

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification (acc. to GB CLP)

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.10	acute toxicity (oral)	4	Acute Tox. 4	H302
3.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373

For full text of H-phrases: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure.

Safety Data Sheet


acc. to Regulation (EC) No. 1907/2006 (REACH)

Transition document following GB exit from the EU

Organic G11-ALU Coolant -36 LL

Version number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Dipotassium tetraborate	CAS No 1332-77-0 EC No 215-575-5	1 - < 2.5	Repr. 2 / H361d		

Name of substance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
ethanediol	CAS No 107-21-1 EC No 203-473-3	-	-	500 mg/kg	oral
Dipotassium tetraborate	CAS No 1332-77-0 EC No 215-575-5	Repr. 2; H361: C ≥ 5.2 %	-	-	

Remarks

All the percentages given are percentages by weight unless stated otherwise. For full text of H-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Take off immediately all contaminated clothing. In case of accident or if you feel unwell, seek medical advice immediately (show the label or safety data sheet where possible).

Following inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician.

Following skin contact

Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

Following eye contact

Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Following ingestion

Rinse mouth with water (only if the person is conscious). Induce vomiting when the affected person is not unconscious. Call a POISON CENTER/doctor.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

For specialist advice physicians should contact the poison centre.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water mist; Alcohol resistant foam; Dry extinguishing powder; Carbon dioxide (CO₂);
Co-ordinate firefighting measures to the fire surroundings.

Organic G11-ALU Coolant -36 LL

Version number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

Unsuitable extinguishing media

Water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

During fire hazardous fumes/smoke could be produced. Carbon monoxide (CO), carbon dioxide (CO₂).

5.3 Advice for firefighters

Keep containers cool with water spray. In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

Self-contained breathing apparatus (SCBA). Standard protective clothing for firefighters.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety. Ventilate affected area.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Use personal protective equipment as required.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Bunding. Covering of drains.

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Absorbent material (e.g. sand, diatomaceous earth, acid binder, universal binder, sawdust, etc.). Clean up by means of pumps (use an explosion-proof or hand pump).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Wash contaminated clothing before reuse. Never keep food or drink in the vicinity of chemicals.

Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feeding-stuffs.

Organic G11-ALU Coolant -36 LL

Version number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- flammability hazards

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- incompatible substances or mixtures

Keep away from alkalis, oxidising substances, acids.

Control of effects

Protect against external exposure, such as

High temperatures, UV-radiation/sunlight, frost.

Consideration of other advice

Keep in a cool place. Store in a dry place. Store in a well-ventilated place. Keep container tightly closed.

- packaging compatibilities

Keep only in original container.

7.3 Specific end use(s)

There is no additional information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Notation	Source
GB	ethane-1,2-diol	107-21-1	WEL		10			H, particle	EH40/2005
GB	ethane-1,2-diol	107-21-1	WEL	20	52	40	104	vap	EH40/2005

Notation

H absorbed through the skin

particle as airborne particles

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

vap as vapours

Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
ethanediol	107-21-1	DNEL	35 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
ethanediol	107-21-1	DNEL	106 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
ethanediol	107-21-1	DNEL	7 mg/m ³	human, inhalatory	consumer (private households)	chronic - local effects
ethanediol	107-21-1	DNEL	53 mg/kg	human, dermal	consumer (private)	chronic - systemic

Safety Data Sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)

Transition document following GB exit from the EU

Organic G11-ALU Coolant -36 LL

Version number: 2.0
 Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
			bw/day		households)	effects
Sodium benzoate	532-32-1	DNEL	3 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Sodium benzoate	532-32-1	DNEL	0.1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Sodium benzoate	532-32-1	DNEL	62.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Sodium benzoate	532-32-1	DNEL	1.5 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects
Sodium benzoate	532-32-1	DNEL	0.06 mg/m ³	human, inhalatory	consumer (private households)	chronic - local effects
Sodium benzoate	532-32-1	DNEL	31.25 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
Sodium benzoate	532-32-1	DNEL	16.6 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects
Dipotassium tetraborate	1332-77-0	DNEL	7.8 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Dipotassium tetraborate	1332-77-0	DNEL	13.6 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Dipotassium tetraborate	1332-77-0	DNEL	13.6 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Dipotassium tetraborate	1332-77-0	DNEL	3.9 mg/m ³	human, inhalatory	consumer (private households)	acute - systemic effects
Dipotassium tetraborate	1332-77-0	DNEL	13.6 mg/m ³	human, inhalatory	consumer (private households)	chronic - local effects
Dipotassium tetraborate	1332-77-0	DNEL	13.6 mg/m ³	human, inhalatory	consumer (private households)	acute - local effects
Dipotassium tetraborate	1332-77-0	DNEL	0.92 mg/kg bw/day	human, oral	consumer (private households)	acute - systemic effects
Dipotassium tetraborate	1332-77-0	DNEL	7.8 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Dipotassium tetraborate	1332-77-0	DNEL	367.7 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Dipotassium tetraborate	1332-77-0	DNEL	3.9 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects
Dipotassium tetraborate	1332-77-0	DNEL	185.6 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
Dipotassium tetraborate	1332-77-0	DNEL	0.92 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects

Organic G11-ALU Coolant -36 LL

 Version number: 2.0
 Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
ethanediol	107-21-1	PNEC	10 mg/l	aquatic organisms	water	intermittent release
ethanediol	107-21-1	PNEC	10 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethanediol	107-21-1	PNEC	1 mg/l	aquatic organisms	marine water	short-term (single instance)
ethanediol	107-21-1	PNEC	199.5 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethanediol	107-21-1	PNEC	37 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ethanediol	107-21-1	PNEC	3.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
ethanediol	107-21-1	PNEC	1.53 mg/kg	terrestrial organisms	soil	short-term (single instance)
Sodium benzoate	532-32-1	PNEC	305 µg/l	aquatic organisms	water	intermittent release
Sodium benzoate	532-32-1	PNEC	0.581 mg/l	aquatic organisms	freshwater	short-term (single instance)
Sodium benzoate	532-32-1	PNEC	0.058 mg/l	aquatic organisms	marine water	short-term (single instance)
Sodium benzoate	532-32-1	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Sodium benzoate	532-32-1	PNEC	2.5 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Sodium benzoate	532-32-1	PNEC	0.25 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Sodium benzoate	532-32-1	PNEC	0.159 mg/kg	terrestrial organisms	soil	short-term (single instance)
Dipotassium tetraborate	1332-77-0	PNEC	2.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
Dipotassium tetraborate	1332-77-0	PNEC	2.9 mg/l	aquatic organisms	marine water	short-term (single instance)
Dipotassium tetraborate	1332-77-0	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Dipotassium tetraborate	1332-77-0	PNEC	5.7 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation. Provide eyewash stations and safety showers at the workplace.

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection

Skin protection



Chemical protective clothing.

Organic G11-ALU Coolant -36 LL

Version number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

Hand protection



Wear suitable gloves. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- type of material

Nitrile rubber, NP: neoprene

- material thickness

Use gloves with a minimum material thickness: ≥ 0.3 mm.

- breakthrough time of the glove material

Use gloves with a minimum breakthrough time of the glove material: >480 minutes (permeation: level 6).

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Type: ABEK-P2 (combined filters against gases, vapours and particles, colour code: Brown/Grey/Yellow/Green/White).

Environmental exposure controls

Take appropriate precautions to avoid uncontrolled release into the environment. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	green
Odour	characteristic
Melting point/freezing point	-36 °C
Boiling point or initial boiling point and boiling range	100 °C calculated value, referring to a component of the mixture
Evaporation rate	not determined
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	LEL: UEL: not determined
Flash point	no data available
Auto-ignition temperature	398 °C (auto-ignition temperature (liquids and gases)) calculated value, referring to a component of the mixture
Decomposition temperature	no data available
pH (value)	not determined
Kinematic viscosity	not determined

Solubility

Water solubility	miscible in any proportion
------------------	----------------------------

Organic G11-ALU Coolant -36 LLVersion number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	2.3 kPa at 20 °C calculated value, referring to a component of the mixture
-----------------	---

Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

9.2 Other information

There is no additional information.

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
--	---

Other safety characteristics

Miscibility	Completely miscible with water.
-------------	---------------------------------

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material is not reactive under normal ambient conditions.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS**Acute toxicity**

Harmful if swallowed.

Safety Data Sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)

Transition document following GB exit from the EU

Organic G11-ALU Coolant -36 LL

Version number: 2.0
 Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

- acute toxicity estimate (ATE)

Exposure route	ATE
Oral	1,053 mg/kg

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
ethanediol	107-21-1	oral	500 mg/kg

Acute toxicity of components

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
ethanediol	107-21-1	oral	LD50	7,712 mg/kg	rat
ethanediol	107-21-1	dermal	LD50	>3,500 mg/kg	mouse
Sodium benzoate	532-32-1	inhalation: dust/mist	LC50	>12,200 mg/m ³ /4h	rat
Sodium benzoate	532-32-1	dermal	LD50	>2,000 mg/kg	rabbit
Dipotassium tetraborate	1332-77-0	oral	LD50	>2,500 mg/kg	rat
Dipotassium tetraborate	1332-77-0	dermal	LD50	>2,000 mg/kg	rabbit

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs (kidney) through prolonged or repeated exposure (if swallowed).

Hazard category	Target organ	Exposure route
2	kidney	if swallowed

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

Organic G11-ALU Coolant -36 LL

 Version number: 2.0
 Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ethanediol	107-21-1	ErC50	<13,000 mg/l	algae	96 h
ethanediol	107-21-1	LC50	53,000 mg/l	fish	96 h
ethanediol	107-21-1	EC50	>100 mg/l	aquatic invertebrates	48 h
ethanediol	107-21-1	NOEC	>100 mg/l	algae	72 h
Sodium benzoate	532-32-1	LC50	484 mg/l	fish	96 h
Sodium benzoate	532-32-1	ErC50	>30.5 mg/l	algae	72 h
Sodium benzoate	532-32-1	NOEC	392.5 mg/l	fish	96 h
Sodium benzoate	532-32-1	growth rate (Er-Cx) 10%	6.5 mg/l	algae	72 h
Dipotassium tetraborate	1332-77-0	LC50	133 mg/l	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
ethanediol	107-21-1	EC50	>15,000 mg/l	aquatic invertebrates	21 d
ethanediol	107-21-1	LC50	>1,500 mg/l	fish	28 d
ethanediol	107-21-1	NOEC	>40 mg/l	fish	28 d
ethanediol	107-21-1	growth (EbCx) 20%	>1,995 mg/l	microorganisms	30 min
Sodium benzoate	532-32-1	LC50	1,500 mg/l	fish	24 h
Sodium benzoate	532-32-1	EC50	>5.81 mg/l	aquatic invertebrates	21 d
Sodium benzoate	532-32-1	NOEC	5.81 mg/l	aquatic invertebrates	21 d
Sodium benzoate	532-32-1	LOEC	>5.81 mg/l	aquatic invertebrates	21 d
Sodium benzoate	532-32-1	growth (EbCx) 10%	>5.81 mg/l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Data are not available.

Degradability of components					
Name of substance	CAS No	Process	Degradation rate	Time	Method
ethanediol	107-21-1	DOC removal	90 - 100 %	10 d	
ethanediol	107-21-1	oxygen depletion	≥83 %	14 d	
Sodium benzoate	532-32-1	carbon dioxide generation	88 %	28 d	

Organic G11-ALU Coolant -36 LLVersion number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
ethanediol	107-21-1		-1.36	
Sodium benzoate	532-32-1		1.88	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessmentDoes not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.**12.6 Endocrine disrupting properties**Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.**12.7 Other adverse effects**

Data are not available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- | | |
|---|---|
| 14.1 UN number | not subject to transport regulations |
| 14.2 UN proper shipping name | not relevant |
| 14.3 Transport hazard class(es) | none |
| 14.4 Packing group | not assigned |
| 14.5 Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 Special precautions for user | There is no additional information. |
| 14.7 Maritime transport in bulk according to IMO instruments | No data available. |

Additional information for each of the UN Model Regulations**International Maritime Dangerous Goods Code (IMDG) - additional information**

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Not subject to ICAO-IATA.

Organic G11-ALU Coolant -36 LL

Version number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

None of the ingredients are listed.

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Dipotassium tetraborate	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	
Dipotassium tetraborate	Metals and their compounds		a)	

Legend

a) Indicative list of the main pollutants

Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013

None of the ingredients are listed.

Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

National regulations (GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

None of the ingredients are listed.

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name	Name acc. to inventory	Conditions of restriction	No
Organic G11-ALU Coolant -36 LL	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC	R3	3

Legend

R3 1. Shall not be used in:
— ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and

Organic G11-ALU Coolant -36 LL

Version number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

Legend

- ashtrays,
— tricks and jokes,
— games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
2. Articles not complying with paragraph 1 shall not be placed on the market.
3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
— can be used as fuel in decorative oil lamps for supply to the general public, and,
— present an aspiration hazard and are labelled with R65 or H304,
4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the British Standard Specification on Decorative oil lamps (BS EN 14059) adopted by the British Standards Institute.
5. Without prejudice to the implementation of other legislation relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
(a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010 'Just a sip of lamp oil
— or even sucking the wick of lamps
— may lead to life-threatening lung damage';
(b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life-threatening lung damage';
(c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the Agency.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
2.2		- precautionary statements: change in the listing (table)
2.3	Other hazards: There is no additional information.	Other hazards
2.3	Results of PBT and vPvB assessment: Does not contain any substances that are assessed to be a PBT or a vPvB $\geq 0.1\%$.	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.
2.3	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.
3.2		Mixtures: change in the listing (table)
3.2		Mixtures: change in the listing (table)
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)
8.1		Relevant DNELs of components of the mixture: change in the listing (table)
8.1		Relevant PNECs of components: change in the listing (table)
8.2	Appropriate engineering controls: General ventilation.	Appropriate engineering controls: General ventilation. Provide eyewash stations and safety showers at the workplace.
8.2	Eye/face protection: eye protection must be worn Use safety goggle with side protection	Eye/face protection: eye protection must be worn Use safety goggle with side protection
8.2	Skin protection:	Skin protection:

Safety Data Sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)

Transition document following GB exit from the EU

Organic G11-ALU Coolant -36 LL

 Version number: 2.0
 Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

Section	Former entry (text/value)	Actual entry (text/value)
	wear protective clothing Chemical protective clothing.	wear protective clothing Chemical protective clothing.
8.2	Hand protection: safety gloves must be worn Wear suitable gloves. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.	Hand protection: safety gloves must be worn Wear suitable gloves. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
8.2	- other protection measures: Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling. Provide eyewash stations and safety showers at the workplace.	- other protection measures: Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.
9.1	Melting point/freezing point: not determined	Melting point/freezing point: -36 °C
9.1	Flash point: not determined	Flash point: no data available
9.1	Auto-ignition temperature: 412 °C (auto-ignition temperature (liquids and gases)) calculated value, referring to a component of the mixture	Auto-ignition temperature: 398 °C (auto-ignition temperature (liquids and gases)) calculated value, referring to a component of the mixture
9.1	Vapour pressure: 100 Pa at 51.1 °C calculated value, referring to a component of the mixture	Vapour pressure: 2.3 kPa at 20 °C calculated value, referring to a component of the mixture
9.1		Density and/or relative density
9.1		Relative vapour density: information on this property is not available
11.1	Acute toxicity of components of the mixture	
11.1		Acute toxicity of components: change in the listing (table)
11.2	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)
12.2		Degradability of components: change in the listing (table)
12.5	Results of PBT and vPvB assessment: Does not contain any substances that are assessed to be a PBT or a vPvB $\geq 0.1\%$.	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.
12.6	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.
15.1		List of pollutants (WFD): change in the listing (table)
16		Abbreviations and acronyms:

Safety Data Sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)

Transition document following GB exit from the EU

Organic G11-ALU Coolant -36 LL

Version number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

Section	Former entry (text/value)	Actual entry (text/value)
		change in the listing (table)

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)

Safety Data Sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)

Transition document following GB exit from the EU

Organic G11-ALU Coolant -36 LL

Version number: 2.0
Replaces version of: 2022-08-09 (1)

Revision: 2024-08-06

Abbr.	Descriptions of used abbreviations
LOEC	Lowest Observed Effect Concentration
log KOW	n-Octanol/water
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Repr.	Reproductive toxicity
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended). The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended). GB mandatory classification and labelling.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs (kidney) through prolonged or repeated exposure (if swallowed).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.